

(19) World Intellectual Property Organization  
International Bureau




(43) International Publication Date  
27 December 2001 (27.12.2001)

PCT

(10) International Publication Number  
**WO 01/97597 A1**

- (51) International Patent Classification<sup>7</sup>: A01G 23/099 (74) Agent: PADEE, Grazyna; ul. Noakowskiego 18/20, PL-00-668 Warszawa (PL).
- (21) International Application Number: PCT/PL00/00053 (81) Designated States (*national*): AT, BG, BR, BY, CA, CH, CZ, DE, DK, EE, ES, FI, HR, HU, ID, IL, IT, LU, MK, NO, PT, RO, RU, SE, SI, SK, TR, UA, US, YU, ZA.
- (22) International Filing Date: 3 August 2000 (03.08.2000) (84) Designated States (*regional*): European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE).
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data: P.340863 19 June 2000 (19.06.2000) PL Published:  
— with international search report
- (71) Applicants and (72) Inventors: KAWALEC, Maria [PL/PL]; ul. Marszałkowska 56/1, PL-00-545 Warszawa (PL). KAWALEC, Andrzej [PL/PL]; ul. Korfańskiego 44, PL-01-496 Warszawa (PL).
- For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.
- (72) Inventor; and (75) Inventor/Applicant (*for US only*): KOSILO, Tomasz [PL/PL]; ul. Hirszfelda 8/9, PL-02-776 Warszawa (PL).

(54) Title: MARKING ELEMENT FOR STAMPING WOOD



(57) Abstract: A marking element for stamping wood comprising a plate (5) provided with catches (3, 6) and with encoded information to be automatically read by a portable reader device (2), characterised in that the element contains inside it a RFID type transponder enabling data writing and reading.

WO 01/97597 A1

### Marking element for stamping wood

The invention relates to a marking element for marking and identification of timber material, such as tree trunks, timber, logs, pallets, etc.

Numerous methods for marking wood are long known, the Signumat method among others. The method is based on marking individual pieces of wood with plates made of plastics, wood or metal. The plates are permanently attached to the wood. The plates are provided with graphic, letter and/or digital signs to identify an object the plate is attached to. Generally the plates are marked with the consecutive number of the gained wood and the encoded sign indicating a source of the material. The marking system is aimed at the wood legality control, as well as improving timber distribution.

The plates used in the known methods must be produced of materials resistant to the weather conditions. Special catches provided with the profiled locking endings secure reliable attachment of the plates. The catches are of a different shape depending on the end use. To mark the front surface of a trunk, a plate with catches in a form of a wave are recommended, whereas for the side surface plates with four pins are used. The other side of plates is provided with corner catches to fasten the plate to

a hammer or another fastening device used to drive plates into the timber material. The most popular plates and fastening devices are produced by Latschbacher, Fluegel and Equip Bois.

Marking plates with various catch shapes have been disclosed in the following patents and patent applications: AT 396410B, EP 0460256A1, PL P-314955, as well as in Polish application for design No 105185. According to the design the plate for marking trees is rectangular. In the vicinity of the shorter edges the plate is provided with the two symmetrically placed corrugated catches in a perpendicular relation to the plate. There are two holes through the plate between the shorter edges of the plate and the corrugated catches. The front of the plate is provided with the corner projections in a form of small poles.

Known marking elements are provided at the front side thereof with a signature as a combination of letters and/or digits. The signature may also have a form of a bar-code. Such embodiment is disclosed in European Patent EP 0248928, wherein the information provided on the element attached to the timber material may be decoded automatically by a portable reader device. According to the above-mentioned description the information can be encoded as a bar-code marked as signs marking off with colour, or in a form of cavities, indents, embossments and protrusions in the plate material, or as a magnetic code carrier placed on or inserted into the plate, such as a magnetic plate, strip, foil or powder. The encoding of information has made it possible to extend the scope of information placed on the plate and to enhance its readout process. The solution provided by EP 0248928 enables, however, to read the write-once information only. Thus, this is a system of unidirectional communication. There is no possibility to supplement the information or to change any part of the

record. Hence, this is the way to encode the information concerning unchanging characteristics of timber (assortment, grade, size), but not the information on the place and period of storage, transport and consignee of the wood. The information can be read from a small distance only. The serious problem is a little resistance of a bar-code to the soil, that is important when using marking elements in the outside, where they are constantly under an influence of frequently aggressive environmental factors. A soiled bar-code may be impossible to read.

There are known some remote identification devices, that make use of radio frequencies RFID (Radio Frequency Identification), based on magnetic or electromagnetic coupling. They contain an unique encoded sequence (binary series) to identify the considered object. The information is encoded in an element called a transponder, and is read by a special reader.

The wood marking element of the invention, comprising a plate provided with catches and with encoded information to be automatically read by a portable reader device, is characterised by containing inside the element a RFID type transponder enabling data writing and reading. The transponder comprises at least one integrated circuit and an antenna to enable communication. The transponder may be inserted, set or impressed into the marking element.

A proper reader is used to write and read from the transponder. The reader generates high frequency magnetic field to exchange information between the reader and the transponder. The magnetic field of the reader provides also energy to power electronic circuits of the transponder, thus the marking element with the transponder need not be supplied with a battery. Digital data transmission is based on a magnetic field modulation.

The method of the invention allows to extend the useful characteristics of marking elements attached to the timber material. The spectrum of information deposited on the marking element may now be much wider. One may write down not only the data on the kind of wood, trunk parameters, and place of origin, but also on a destination, consignee, time and route of transport, and many others. It is very important that for the first time there is a possibility not only to read a permanently written information, but also to supplement and change it. The information placed in the transponder is fully resistant to soil and varying weather conditions. Depending on the construction of a reader it is possible to read and write data from a distance of several centimetres up to about 1 m. It is possible to transmit data through the obstacles to remotely identify objects and remotely write and modify data. The above-named advantages are of great importance in the circumstances of wood hewing, storing, handling and processing, frequently in an unfavourable weather conditions and in a hardly accessible places. The data in the element of the invention are very well secured against an unauthorised reading and modification; it can be encoded and invisible. This advantage according to the invention facilitates discovering of illegal hewing, stealing and processing of wood and preventing the same.

The transponder placed in the marking element of the invention needs not to be maintained or serviced and activates (switches on) on detecting the magnetic field of the reader.

The marking element of the invention may be additionally provided with information in a form of known digital and/or letter writing.

The marking element of the invention is shown in one embodiment on the drawings, wherein Fig. 1 illustrates the element in a view from a side

containing the information, and Fig. 2 illustrates a cross-section of the element and the reader, but at the same time the invention is not limited to this embodiment.

The marking element of the invention comprises the rectangular plate 5 with the information in a form of digits marked on it. The front side of the plate 5 is provided with corner catches 6 to reliably place the plate on a hammer for driving the plate into the timber material. The other side of the plate is provided with corrugated catches 3 placed on the shorter edges of the plate to attach the plate to the timber material. Between the corrugated catches and shorter edges of the plate there are two round holes 4. The transponder RFID 1 is heat pressed into the plate between the corrugated catches. The data from the transponder 5 are read and modified by a reader 2.

According to the invention, the transponder 5 may be placed on any marking element regardless of the construction thereof.

## CLAIMS

1. A marking element for stamping wood comprising a plate provided with catches and with encoded information to be automatically read by a portable reader device, characterised in that the element contains inside it a RFID type transponder enabling data writing and reading.
2. The element according to claim 1, characterised in that the transponder comprises at least one integrated circuit and an antenna to enable communication.
3. The element according to claim 1, characterised in that the transponder is inserted, set or impressed into the marking element.




Fig. 1




Fig. 2



## INTERNATIONAL SEARCH REPORT

International Application No

PCT/PL 00/00053

## A. CLASSIFICATION OF SUBJECT MATTER

IPC 7 A01G23/099

According to International Patent Classification (IPC) or to both national classification and IPC

## B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 A01G A01K G06K G09F

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal, WPI Data

## C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	FR 2 763 164 A (LEUVREY EDWIGE KARINE LAURENCE) 13 November 1998 (1998-11-13) the whole document	1,3
A	---	2
Y	EP 0 248 928 A (LATSCHBACHER KAJETAN) 16 December 1987 (1987-12-16) cited in the application the whole document	1-3
Y	EP 0 535 919 A (RYAN MICHAEL C) 7 April 1993 (1993-04-07) column 2, line 35 -column 6, line 43; figures --- -/--	1-3

☒ Further documents are listed in the continuation of box C.☒ Patent family members are listed in annex.

## \* Special categories of cited documents :

\*A\* document defining the general state of the art which is not considered to be of particular relevance

\*E\* earlier document but published on or after the international filing date

\*L\* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

\*O\* document referring to an oral disclosure, use, exhibition or other means

\*P\* document published prior to the international filing date but later than the priority date claimed

\*T\* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

\*X\* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

\*Y\* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

\*G\* document member of the same patent family

Date of the actual completion of the international search

21 March 2001

Date of mailing of the international search report

28/03/2001

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2  
NL - 2280 HV Rijswijk  
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,  
Fax: (+31-70) 340-3016

Authorized officer

Merckx, A

## INTERNATIONAL SEARCH REPORT

Int. Patent Application No  
PCT/PL 00/00053

## C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	DE 198 07 284 A (JURISCH ; PEITSCH (DE); SEMMLER (DE)) 9 September 1999 (1999-09-09) the whole document ---	1-3
A	GB 2 294 846 A (KERBY ROBERT ANTHONY) 8 May 1996 (1996-05-08) claims 1,11; figures ---	1,3
A	GB 2 075 464 A (LATSCHBACHER KAJETAN) 18 November 1981 (1981-11-18) ---	
A	WO 96 32706 A (LATSCHBACHER KLAUS) 17 October 1996 (1996-10-17) & PL 314 955 A 20 January 1997 (1997-01-20) cited in the application -----	

## INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/PL 00/00053

Patent document cited in search report		Publication date	Patent family member(s)		Publication date
FR 2763164	A	13-11-1998	NONE		
EP 0248928	A	16-12-1987	DK	456286 A	11-12-1987
			GR	862479 A	26-01-1987
			YU	173686 A	28-01-1991
EP 0535919	A	07-04-1993	CA	2079517 A	02-04-1993
DE 19807284	A	09-09-1999	DE	19912806 A	21-09-2000
GB 2294846	A	08-05-1996	NONE		
GB 2075464	A	18-11-1981	NONE		
WO 9632706	A	17-10-1996	PL	314955 A	20-01-1997

